

# Contents

Information center commands .....	1
diagnostic-logfile save .....	1
display diagnostic-logfile summary .....	1
display info-center .....	2
display logbuffer .....	3
display logfile summary .....	4
display logfile summary .....	5
display security-logfile summary .....	6
enable log updown .....	6
info-center diagnostic-logfile directory .....	7
info-center diagnostic-logfile enable .....	8
info-center diagnostic-logfile frequency .....	8
info-center diagnostic-logfile quota .....	9
info-center enable .....	9
info-center format .....	10
info-center logbuffer .....	10
info-center logbuffer size .....	11
info-center logfile directory .....	11
info-center logfile enable .....	12
info-center logfile frequency .....	13
info-center logfile overwrite-protection .....	13
info-center logfile size-quota .....	14
info-center logging suppress duplicates .....	14
info-center logging suppress module .....	16
info-center loghost .....	17
info-center loghost source .....	18
info-center security-logfile alarm-threshold .....	18
info-center security-logfile directory .....	19
info-center security-logfile enable .....	19
info-center security-logfile frequency .....	20
info-center security-logfile size-quota .....	21
info-center source .....	21
info-center synchronous .....	23
info-center syslog min-age .....	24
info-center syslog trap buffersize .....	24
info-center timestamp .....	25
info-center timestamp loghost .....	26
info-center trace-logfile quota .....	26
logfile save .....	27
reset logbuffer .....	27
security-logfile save .....	28
snmp-agent trap enable syslog .....	28
terminal debugging .....	29
terminal logging level .....	30
terminal monitor .....	31

# Information center commands

The device supports the FIPS mode that complies with NIST FIPS 140-2 requirements. Support for features, commands, and parameters might differ in FIPS mode and non-FIPS mode. For more information about FIPS mode, see *Security Configuration Guide*.

## diagnostic-logfile save

Use **diagnostic-logfile save** to manually save diagnostic logs from the diagnostic log file buffer to the diagnostic log file.

### Syntax

**diagnostic-logfile save**

### Views

Any view

### Predefined user roles

network-admin

### Usage guidelines

You can specify the directory to save the diagnostic log file by using the **info-center diagnostic-logfile directory** command.

The system clears the diagnostic log file buffer after saving the buffered diagnostic logs to the diagnostic log file.

If the diagnostic log file buffer is empty, this command displays a success message event though no logs are saved to the diagnostic log file.

### Examples

```
# Manually save diagnostic logs from the diagnostic log file buffer to the diagnostic log file.
```

```
<Sysname> diagnostic-logfile save
```

```
The contents in the diagnostic log file buffer have been saved to the file  
flash:/diagfile/diagfile.log.
```

### Related commands

**info-center diagnostic-logfile enable**

**info-center diagnostic-logfile directory**

## display diagnostic-logfile summary

Use **display diagnostic-logfile summary** to display the diagnostic log file configuration.

### Syntax

**display diagnostic-logfile summary**

### Views

Any view

### Predefined user roles

network-admin

network-operator

## Examples

```
# Display the diagnostic log file configuration.
<Sysname> display diagnostic-logfile summary
Diagnostic log file: Enabled.
Diagnostic log file size quota: 10 MB
Diagnostic log file directory: flash:/diagfile
Writing frequency: 24 hour 0 min 0 sec
```

**Table 1 Command output**

Field	Description
Diagnostic log file	Status of the diagnostic log file: <ul style="list-style-type: none"><li>• <b>Enabled</b>—Diagnostic logs can be output to the diagnostic log file.</li><li>• <b>Disabled</b>—Diagnostic logs cannot be output to the diagnostic log file.</li></ul>
Diagnostic log file size quota	Maximum size for the diagnostic log file, in MB.
Log file directory	Directory where the diagnostic log file is saved.
Writing frequency	Interval at which the system saves diagnostic logs from the buffer to the diagnostic log file.

## display info-center

Use **display info-center** to display information center configuration.

### Syntax

```
display info-center
```

### Views

Any view

### Predefined user roles

network-admin  
network-operator

### Examples

```
# Display information center configuration.
<Sysname> display info-center
Information Center: Enabled
Console: Enabled
Monitor: Enabled
Log host: Enabled
    192.168.0.1,
    port number: 5000, host facility: local7
Log buffer: Enabled
    Max buffer size 1024, current buffer size 512,
    Current messages 0, dropped messages 0, overwritten messages 0
Log file: Enabled
Security log file: Enabled
Information timestamp format:
```

Log host: Date

Other output destination: Date

## display logbuffer

Use **display logbuffer** to display the state of the log buffer and the log information in the log buffer.

### Syntax

```
display logbuffer [ reverse ] [ level severity | size buffersize | slot slot-number ] *
```

### Views

Any view

### Predefined user roles

network-admin

network-operator

### Parameters

**reverse**: Displays log entries chronologically, with the most recent entry at the top. If you do not specify this keyword, the command displays log entries chronologically, with the oldest entry at the top.

**level severity**: Specifies a severity level in the range of 0 to 7. If you do not specify a severity level, this command displays log information for all levels.

**Table 2 Log levels**

Severity value	Level	Description	Keyword in commands
0	Emergency	The system is unusable. For example, the system authorization has expired.	<b>emergency</b>
1	Alert	Action must be taken immediately. For example, traffic on an interface exceeds the upper limit.	<b>alert</b>
2	Critical	Critical condition. For example, the device temperature exceeds the upper limit, the power module fails, or the fan tray fails.	<b>critical</b>
3	Error	Error condition. For example, the link state changes.	<b>error</b>
4	Warning	Warning condition. For example, an interface is disconnected, or the memory resources are used up.	<b>warning</b>
5	Notification	Normal but significant condition. For example, a terminal logs in to the device, or the device reboots.	<b>notification</b>
6	Informational	Informational message. For example, a command or a <b>ping</b> operation is executed.	<b>informational</b>
7	Debugging	Debugging message.	<b>debugging</b>

**size buffersize**: Specifies the number of latest logs to be displayed. The value range is 1 to 1024. If you do not specify this option, the command displays all logs in the log buffer.

**slot slot-number**: Specifies an IRF member device by its member ID. If you do not specify a member device, this command displays information for all member devices.

### Examples

```
# Display the state and log information of the log buffer.
```

```
<Sysname> display logbuffer
```

```

Log buffer: Enabled
Max buffer size: 1024
Actual buffer size: 512
Dropped messages: 0
Overwritten messages: 718
Current messages: 512
%Jun 17 15:57:09:578 2016 Sysname SYSLOG/7/SYS_RESTART:System restarted --
...

```

**Table 3 Command output**

Field	Description
Log buffer	Status of the log buffer: <ul style="list-style-type: none"> <li>• <b>Enabled</b>—Logs can be output to the log buffer.</li> <li>• <b>Disabled</b>—Logs cannot be output to the buffer.</li> </ul>
Max buffer size	Maximum buffer size supported by the device.
Actual buffer size	Maximum buffer size configured by using the <b>info-center logbuffer size</b> command.
Dropped messages	Number of dropped messages.
Overwritten messages	Number of overwritten messages.
Current messages	Number of current messages.

## Related commands

**info-center logbuffer**

**reset logbuffer**

## display logbuffer summary

Use **display logbuffer summary** to display the summary of the log buffer.

### Syntax

```
display logbuffer summary [ level severity | slot slot-number ] *
```

### Views

Any view

### Predefined user roles

network-admin

network-operator

### Parameters

**level severity**: Specifies a severity level in the range of 0 to 7. If you do not specify a severity level, this command displays log information of all levels in the log buffer. For more information about log levels, see [Table 2](#).

**slot slot-number**: Specifies an IRF member device by its member ID. If you do not specify a member device, this command displays information for all member devices.

### Examples

# Display the summary of the log buffer.

```
<Sysname> display logbuffer summary
```

```

Slot EMERG ALERT  CRIT ERROR  WARN NOTIF  INFO DEBUG
   1   0   0   0   7   0   34   38   0

```

**Table 4 Command output**

Field	Description
EMERG	Represents emergency. For more information, see <a href="#">Table 2</a> .
ALERT	Represents alert. For more information, see <a href="#">Table 2</a> .
CRIT	Represents critical. For more information, see <a href="#">Table 2</a> .
ERROR	Represents error. For more information, see <a href="#">Table 2</a> .
WARN	Represents warning. For more information, see <a href="#">Table 2</a> .
NOTIF	Represents notification. For more information, see <a href="#">Table 2</a> .
INFO	Represents informational. For more information, see <a href="#">Table 2</a> .
DEBUG	Represents debug. For more information, see <a href="#">Table 2</a> .

## display logfile summary

Use **display logfile summary** to display the log file configuration.

### Syntax

```
display logfile summary
```

### Views

Any view

### Predefined user roles

```
network-admin
network-operator
```

### Examples

```
# Display the log file configuration.
<Sysname> display logfile summary
  Log file: Enabled.
  Log file size quota: 10 MB
  Log file directory: flash:/logfile
  Writing frequency: 24 hour 0 min 10 sec
```

**Table 5 Command output**

Field	Description
Log file	Log file status: <ul style="list-style-type: none"> <li>• <b>Enabled</b>—Logs can be output to a log file.</li> <li>• <b>Disabled</b>—Logs cannot be output to a log file.</li> </ul>
Log file size quota	Maximum storage space reserved for a log file, in MB.
Log file directory	Log file directory.
Writing frequency	Log file writing frequency.

# display security-logfile summary

Use **display security-logfile summary** to display the summary of the security log file.

## Syntax

**display security-logfile summary**

## Views

Any view

## Predefined user roles

security-audit

## Usage guidelines

To use this command, a local user must have the security-audit user role. For information about configuring the security-audit user role, see *Security Command Reference*.

## Examples

```
# Display the summary of the security log file.
<Sysname> display security-logfile summary
  Security log file: Enabled
  Security log file size quota: 10 MB
  Security log file directory: flash:/seclog
  Alarm threshold: 80%
  Current usage: 30%
  Writing frequency: 24 hour 0 min 0 sec
```

**Table 6 Command output**

Field	Description
Security log file	Status of the security log file: <ul style="list-style-type: none"><li>• <b>Enabled</b>—Security logs can be output to the security log file.</li><li>• <b>Disabled</b>—Security logs cannot be output to the security log file.</li></ul>
Security log file size quota	Maximum storage space reserved for the security log file.
Security log file directory	Security log file directory.
Alarm-threshold	Alarm threshold of the security log file usage.
Current usage	Current usage of the security log file.
Writing frequency	Security log file writing frequency.

## Related commands

**authorization-attribute** (*Security Command Reference*)

# enable log updown

Use **enable log updown** to enable an interface to generate link up or link down logs when the interface state changes.

Use **undo enable log updown** to disable an interface from generating link up or link down logs when the interface state changes.

## Syntax

**enable log updown**  
**undo enable log updown**

## Default

All interfaces are allowed to generate link up and link down logs.

## Views

Interface view

## Predefined user roles

network-admin

## Examples

```
# Disable Ten-GigabitEthernet 1/0/1 from generating link up or link down logs.
<Sysname> system-view
[Sysname] interface ten-gigabitethernet 1/0/1
[Sysname-Ten-GigabitEthernet1/0/1] undo enable log updown
```

# info-center diagnostic-logfile directory

Use **info-center diagnostic-logfile directory** to configure the directory to save the diagnostic log file.

## Syntax

**info-center diagnostic-logfile directory** *dir-name*

## Default

The diagnostic log file directory is **flash:/diagfile**.

## Views

System view

## Predefined user roles

network-admin

## Parameters

*dir-name*: Specifies a directory by its name, a string of 1 to 64 characters.

## Usage guidelines

The specified directory must have been created.

This command cannot survive an IRF reboot or a master/subordinate switchover.

## Examples

```
# Set the diagnostic log file directory to flash:/test.
<Sysname> mkdir test
Creating directory flash:/test... Done.
<Sysname> system-view
[Sysname] info-center diagnostic-logfile directory flash:/test
```

## info-center diagnostic-logfile enable

Use **info-center diagnostic-logfile enable** to enable saving diagnostic logs to the diagnostic log file.

Use **undo info-center diagnostic-logfile enable** to disable saving diagnostic logs to the diagnostic log file.

### Syntax

**info-center diagnostic-logfile enable**

**undo info-center diagnostic-logfile enable**

### Default

Saving diagnostic logs to the diagnostic log file is enabled.

### Views

System view

### Predefined user roles

network-admin

### Usage guidelines

This command enables saving diagnostic logs to the diagnostic log file for centralized management. Users can view the diagnostic logs to monitor device activities and to troubleshoot problems.

### Examples

```
# Enable saving diagnostic logs to the diagnostic log file.  
<Sysname> system-view  
[Sysname] info-center diagnostic-logfile enable
```

## info-center diagnostic-logfile frequency

Use **info-center diagnostic-logfile frequency** to configure the interval at which the system saves diagnostic logs from the diagnostic log file buffer to the diagnostic log file.

Use **undo info-center diagnostic-logfile frequency** to restore the default.

### Syntax

**info-center diagnostic-logfile frequency** *freq-sec*

**undo info-center diagnostic-logfile frequency**

### Default

The diagnostic log file saving interval is 86400 seconds.

### Views

System view

### Predefined user roles

network-admin

### Parameters

*freq-sec*: Specifies the diagnostic log file saving interval in seconds. The value range is 10 to 86400.

### Usage guidelines

The system outputs diagnostic logs to the diagnostic log file buffer, and then saves the buffered logs to the diagnostic log file at the specified interval.

## Examples

```
# Set the diagnostic log file saving interval to 600 seconds.
<Sysname> system-view
[Sysname] info-center diagnostic-logfile frequency 600
```

## Related commands

**info-center diagnostic-logfile enable**

# info-center diagnostic-logfile quota

Use **info-center diagnostic-logfile quota** to set the maximum size for the diagnostic log file.

Use **undo info-center diagnostic-logfile quota** to restore the default.

## Syntax

```
info-center diagnostic-logfile quota size
undo info-center diagnostic-logfile quota
```

## Default

The maximum size for the diagnostic log file is 10 MB.

## Views

System view

## Predefined user roles

network-admin

## Parameters

*size*: Specifies the maximum size for the diagnostic log file, in MB. The value range is 1 to 10.

## Examples

```
# Set the maximum size to 6 MB for the diagnostic log file.
<Sysname> system-view
[Sysname] info-center diagnostic-logfile quota 6
```

# info-center enable

Use **info-center enable** to enable the information center.

Use **undo info-center enable** to disable the information center.

## Syntax

```
info-center enable
undo info-center enable
```

## Default

The information center is enabled.

## Views

System view

## Predefined user roles

network-admin

## Examples

```
# Enable the information center.
<Sysname> system-view
[Sysname] info-center enable
Information center is enabled.
```

## info-center format

Use **info-center format** to set the format for logs sent to log hosts.

Use **undo info-center format** to restore the default.

### Syntax

```
info-center format { cmcc | unicom }
```

```
undo info-center format
```

### Default

Logs are sent to log hosts in standard format.

### Views

System view

### Predefined user roles

network-admin

### Parameters

**cmcc**: Specifies the China Mobile Communications Corporation (**cmcc**) format.

**unicom**: Specifies the China Unicom (**unicom**) format.

### Usage guidelines

Logs can be sent to log hosts in standard, **unicom**, or **cmcc** format. For more information about log formats, see *Network Management and Monitoring Configuration Guide*.

## Examples

```
# Set the log format to unicom for logs sent to log hosts.
<Sysname> system-view
[Sysname] info-center format unicom
```

## info-center logbuffer

Use **info-center logbuffer** to enable log output to the log buffer.

Use **undo info-center logbuffer** to disable log output to the log buffer.

### Syntax

```
info-center logbuffer
```

```
undo info-center logbuffer
```

### Default

Log output to the log buffer is enabled.

### Views

System view

## Predefined user roles

network-admin

## Examples

```
# Enable log output to the log buffer.
<Sysname> system-view
[Sysname] info-center logbuffer
```

## Related commands

**display logbuffer**  
**info-center enable**

# info-center logbuffer size

Use **info-center logbuffer size** to set the maximum number of logs that can be stored in the log buffer.

Use **undo info-center logbuffer size** to restore the default.

## Syntax

```
info-center logbuffer size buffersize  
undo info-center logbuffer size
```

## Default

The log buffer can store a maximum of 512 logs.

## Views

System view

## Predefined user roles

network-admin

## Parameters

*buffersize*: Specifies the maximum number of logs that can be stored in the log buffer. The value range is 0 to 1024, and the default is 512.

## Examples

```
# Set the maximum log buffer size to 50.
<Sysname> system-view
[Sysname] info-center logbuffer size 50

# Restore the default maximum log buffer size.
<Sysname> system-view
[Sysname] undo info-center logbuffer size
```

## Related commands

**display logbuffer**  
**info-center enable**

# info-center logfile directory

Use **info-center logfile directory** to specify the directory to save the log file.

## Syntax

**info-center logfile directory** *dir-name*

## Default

The log file directory is **flash:/logfile**.

## Views

System view

## Predefined user roles

network-admin

## Parameters

*dir-name*: Specifies a directory by its name, a string of 1 to 64 characters.

## Usage guidelines

The specified log file directory must have been created.

The log file uses the .log extension.

This command cannot survive an IRF reboot or a master/subordinate switchover.

## Examples

```
# Set the log file directory to flash:/test.
<Sysname> mkdir test
Creating directory flash:/test... Done.
<Sysname> system-view
[Sysname] info-center logfile directory flash:/test
```

## Related commands

**info-center logfile enable**

# info-center logfile enable

Use **info-center logfile enable** to enable the log file feature.

Use **undo info-center logfile enable** to disable the log file feature.

## Syntax

**info-center logfile enable**

**undo info-center logfile enable**

## Default

The log file feature is enabled.

## Views

System view

## Predefined user roles

network-admin

## Examples

```
# Enable log output to the log file.
<Sysname> system-view
[Sysname] info-center logfile enable
```

# info-center logfile frequency

Use **info-center logfile frequency** to configure the interval at which the system saves logs from the log file buffer to the log file.

Use **undo info-center logfile frequency** to restore the default.

## Syntax

**info-center logfile frequency** *freq-sec*

**undo info-center logfile frequency**

## Default

The log file saving interval is 86400 seconds.

## Views

System view

## Predefined user roles

network-admin

## Parameters

*freq-sec*: Specifies the log file saving interval in seconds. The value range is 1 to 86400.

## Usage guidelines

This command enables the system to automatically save logs in the log file buffer to the log file at the specified interval.

## Examples

```
# Set the log file saving interval to 60000 seconds.  
<Sysname> system-view  
[Sysname] info-center logfile frequency 60000
```

## Related commands

**info-center logfile enable**

# info-center logfile overwrite-protection

Use **info-center logfile overwrite-protection** to enable log file overwrite-protection.

Use **undo info-center logfile overwrite-protection** to disable log file overwrite-protection.

## Syntax

**info-center logfile overwrite-protection** [ **all-port-powerdown** ]

**undo info-center logfile overwrite-protection**

## Default

Log file overwrite-protection is disabled.

## Views

System view

## Predefined user roles

network-admin

## Parameters

**all-port-powerdown**: Shuts down all the service ports on the device when no log file space or storage device space is available. If you do not specify this keyword, the device does not shut down service ports when no log file space or storage device space is available.

## Usage guidelines

This command is available only in FIPS mode.

Log file overwrite protection enables the system to stop saving new logs when no log file space or storage device space is available.

## Examples

```
# Enable log file overwrite-protection.  
<Sysname> system-view  
[Sysname] info-center logfile overwrite-protection
```

# info-center logfile size-quota

Use **info-center logfile size-quota** to set the maximum size for the log file.

Use **undo info-center logfile size-quota** to restore the default.

## Syntax

```
info-center logfile size-quota size  
undo info-center logfile size-quota
```

## Default

The maximum size for the log file is 10 MB.

## Views

System view

## Predefined user roles

network-admin

## Parameters

*size*: Specifies the maximum size for the log file, in MB. The value range is 1 to 10.

## Examples

```
# Set the maximum size to 6 MB for the log file.  
<Sysname> system-view  
[Sysname] info-center logfile size-quota 6
```

## Related commands

```
info-center logfile enable
```

# info-center logging suppress duplicates

Use **info-center logging suppress duplicates** to enable duplicate log suppression.

Use **undo info-center logging suppress duplicate** to disable duplicate log suppression.

## Syntax

```
info-center logging suppress duplicates  
undo info-center logging suppress duplicates
```

## Default

Duplicate log suppression is disabled.

## Views

System view

## Predefined user roles

network-admin

## Usage guidelines

Outputting consecutive duplicate logs at an interval of less than 30 seconds wastes system and network resources.

With this feature enabled, the system starts a suppression period when outputting a new log:

- During the suppression period, the system does not output logs with the same module name, level, mnemonic, location, and text as the previous log.
- After the suppression period expires, if the same log continues to appear, the system outputs the suppressed logs and the log number and starts another suppression period. The suppression period is 30 seconds the first time, 2 minutes the second time, and 10 minutes for subsequent times.
- If a different log is generated during the suppression period, the system aborts the current suppression period, outputs suppressed logs and the log number and then outputs the new log, starting another suppression period.

## Examples

Suppose the IP address of VLAN-interface 100 on device A conflicts with the IP address of another device on the network, device A will output the following log information repeatedly:

```
%Jan 1 07:27:48:636 2000 Sysname ARP/6/DUPIFIP:  
Duplicate address 172.16.0.1 on interface Vlan-interface100, sourced from 00e0-0058-123d
```

# Enable duplicate log suppression on device A.

```
<Sysname> system-view  
[Sysname] info-center logging suppress duplicates
```

Device A continues to output the following log information:

```
%Jan 1 07:27:48:636 2000 Sysname ARP/6/DUPIFIP:  
Duplicate address 172.16.0.1 on interface Vlan-interface100, sourced from 00e0-0058-123d  
%Jan 1 07:28:19:639 2000 Sysname ARP/6/DUPIFIP:  
Duplicate address 172.16.0.1 on interface Vlan-interface100, sourced from 00e0-0058-123d  
This message repeated 4 times in last 30 seconds.
```

The output shows that after the duplicate log suppression feature is enabled, the system outputs another duplicate log and starts the first suppression period for 30 seconds.

```
%Jan 1 07:30:19:643 2000 Sysname ARP/6/DUPIFIP:  
Duplicate address 172.16.0.1 on interface Vlan-interface100, sourced from 00e0-0058-123d  
This message repeated 20 times in last 2 minutes.
```

The output shows that the second suppression period lasts for 2 minutes.

```
%Jan 1 07:30:20:541 2000 Sysname ARP/6/DUPIFIP:  
Duplicate address 172.16.0.1 on interface Vlan-interface100, sourced from 00e0-0058-123d  
This message repeated 1 times in last 1 second.  
%Jan 1 07:30:19:542 2000 Sysname CFGMAN/5/CFGMAN_CFGCHANGED:  
-EventIndex=[12]-CommandSource=[2]-ConfigSource=[4]-ConfigDestination=[2];  
Configuration is changed.
```

The output shows that a different log is generated during the suppression period.

```
%Jan 1 07:30:24:643 2000 Sysname ARP/6/DUPIFIP:
Duplicate address 172.16.0.1 on interface Vlan-interface100, sourced from 00e0-0058-123d
%Jan 1 07:30:55:645 2000 Sysname ARP/6/DUPIFIP:
Duplicate address 172.16.0.1 on interface Vlan-interface100, sourced from 00e0-0058-123d
This message repeated 4 times in last 30 seconds.
```

The output shows that the system starts another suppression period.

## info-center logging suppress module

Use **info-center logging suppress module** to configure a log suppression rule for a module.

Use **undo info-center logging suppress module** to delete a log suppression rule.

### Syntax

```
info-center logging suppress module module-name mnemonic { all | mnemonic-value }
undo info-center logging suppress module module-name mnemonic { all | mnemonic-value }
```

### Default

The device does not suppress output of any logs from any modules.

### Views

System view

### Predefined user roles

network-admin

### Parameters

*module-name*: Specifies a log source module by its name, a case-insensitive string of 1 to 8 characters. To view the list of available log source modules, use the **info-center logging suppress module ?** command.

**mnemonic** { **all** | *mnemonic-value* }: Configures a mnemonic filter for log suppression.

- **all**: Suppresses output of all logs of the module.
- *mnemonic-value*: Suppresses output of logs with the specified mnemonic value. The *mnemonic-value* argument is a case-insensitive string of 1 to 32 characters, which must be the complete value contained in the mnemonic field of the log message. Log suppression will fail if a partial mnemonic value is specified.

### Usage guidelines

You can configure log suppression rules to filter out the logs that you are not concerned with. A log suppression rule suppresses output of all logs or only logs with a specific mnemonic value for a module.

### Examples

```
# Configure a log suppression rule to suppress output of logs with the shell_login mnemonic value for the shell module.
```

```
<Sysname> system-view
```

```
[Sysname] info-center logging suppress module shell mnemonic shell_login
```

### Related commands

**info-center source**

# info-center loghost

Use **info-center loghost** to specify a log host and to configure output parameters.

Use **undo info-center loghost** to remove a log host.

## Syntax

```
info-center loghost [ vpn-instance vpn-instance-name ] { hostname | ipv4-address | ipv6 ipv6-address } [ port port-number ] [ dscp dscp-value ] [ facility local-number ]
```

```
undo info-center loghost [ vpn-instance vpn-instance-name ] { hostname | ipv4-address | ipv6 ipv6-address }
```

## Default

No log hosts are specified.

## Views

System view

## Predefined user roles

network-admin

## Parameters

**vpn-instance** *vpn-instance-name*: Specifies an MPLS L3VPN instance by its name, a case-sensitive string of 1 to 31 characters. If the log host is on the public network, do not specify this option.

*hostname*: Specifies a log host by its name, a case-insensitive string of 1 to 253 characters. The host name can contain letters, digits, and special characters including hyphen (-), underscore (\_), and dot (.).

*ipv4-address*: Specifies a log host by its IPv4 address.

**ipv6** *ipv6-address*: Specifies a log host by its IPv6 address.

**port** *port-number*: Specifies the port number of the log host, in the range of 1 to 65535. The default is 514. It must be the same as the value configured on the log host. Otherwise, logs cannot be sent to the log host.

**dscp** *dscp-value*: Specifies the DSCP value to be carried in information center log packets sent to the log host. The DSCP value of a packet defines the priority of the packet and affects the transmission priority of the packet. The value range for the *dscp-value* argument is 0 to 63, and the default is 0. A greater DSCP value represents a higher priority.

**facility** *local-number*: Specifies a logging facility from local0 to local7 for the log host. The default value is local7. Logging facilities are used to mark different logging sources, and query and filer logs.

## Usage guidelines

The **info-center loghost** command takes effect only after the information center is enabled by using **info-center enable** command.

The device supports a maximum of 20 log hosts.

## Examples

```
# Output logs to the log host at 1.1.1.1.  
<Sysname> system-view  
[Sysname] info-center loghost 1.1.1.1
```

## info-center loghost source

Use **info-center loghost source** to specify a source IP address for logs sent to log hosts.

Use **undo info-center loghost source** to restore the default.

### Syntax

**info-center loghost source** *interface-type interface-number*

**undo info-center loghost source**

### Default

The source IP address of logs sent to log hosts is the primary IP address of the outgoing interface.

### Views

System view

### Predefined user roles

network-admin

### Parameters

*interface-type interface-number*. Specifies an interface by its type and number.

### Usage guidelines

The system uses the primary IP address of the specified interface as the source IP address of the logs sent to log hosts.

The **info-center loghost source** command takes effect only after the information center is enabled by using **info-center enable** command.

### Examples

# Use the IP address of interface Loopback 0 as the source IP address of the logs sent to log hosts.

```
<Sysname> system-view
[Sysname] interface loopback 0
[Sysname-LoopBack0] ip address 2.2.2.2 32
[Sysname-LoopBack0] quit
[Sysname] info-center loghost source loopback 0
```

## info-center security-logfile alarm-threshold

Use **info-center security-logfile alarm-threshold** to set the alarm threshold for security log file usage.

Use **undo info-center security-logfile alarm-threshold** to restore the default.

### Syntax

**info-center security-logfile alarm-threshold** *usage*

**undo info-center security-logfile alarm-threshold**

### Default

The alarm threshold for security log file usage is 80. When the usage of the security log file reaches 80%, the system outputs a message to inform the administrator.

### Views

System view

## Predefined user roles

network-admin

## Parameters

*usage*: Specifies an alarm threshold. The value must be an integer in the range of 1 to 100.

## Usage guidelines

When the security log file is full, the system deletes the oldest logs and then writes new logs to the security log file. This feature helps avoid security log loss by setting an alarm threshold for the security log file usage. When the threshold is reached, the system outputs log information to inform the administrator. The administrator can log in to the device with the security-audit user role and back up the security log file.

## Examples

```
# Set the alarm threshold for security log file usage to 90.
<Sysname> system-view
[Sysname] info-center security-logfile alarm-threshold 90
```

## Related commands

**info-center security-logfile size-quota**

# info-center security-logfile directory

Use **info-center security-logfile directory** to specify the security log file directory.

## Syntax

**info-center security-logfile directory** *dir-name*

## Default

The security log file is saved in the **flash:/seclog** directory.

## Views

System view

## Predefined user roles

security-audit

## Parameters

*dir-name*: Specifies a directory by its name, a string of 1 to 64 characters.

## Usage guidelines

The specified directory must have been created.

This command cannot survive an IRF reboot or a master/subordinate switchover.

## Examples

```
# Set the security log file directory to flash:/test.
<Sysname> mkdir test
Creating directory flash:/test... Done.
<Sysname> system-view
[Sysname] info-center security-logfile directory flash:/test
```

# info-center security-logfile enable

Use **info-center security-logfile enable** to enable saving of security logs to the security log file.

Use **undo info-center security-logfile enable** to restore the default.

### Syntax

**info-center security-logfile enable**  
**undo info-center security-logfile enable**

### Default

The saving of security logs to the security log file is disabled.

### Views

System view

### Predefined user roles

network-admin

### Usage guidelines

This feature enables the system to output security logs to the security log file buffer, and then saves the buffered logs to the security log file regularly.

### Examples

```
# Enable saving security logs to the security log file.  
<Sysname> system-view  
[Sysname] info-center security-logfile enable
```

## info-center security-logfile frequency

Use **info-center security-logfile frequency** to configure the interval for saving security logs to the security log file.

Use **undo info-center security-logfile frequency** to restore the default.

### Syntax

**info-center security-logfile frequency** *freq-sec*  
**undo info-center security-logfile frequency**

### Default

The security log file saving interval is 86400 seconds.

### Views

System view

### Predefined user roles

network-admin

### Parameters

*freq-sec*: Specifies the security log file saving interval in seconds. The value range is 10 to 86400 seconds.

### Usage guidelines

The system outputs security logs to the security log file buffer, and then saves the buffered logs to the security log file at the specified interval.

### Examples

```
# Set the security log file saving interval to 600 seconds.  
<Sysname> system-view
```

```
[Sysname] info-center security-logfile frequency 600
```

## Related commands

**info-center security-logfile enable**

# info-center security-logfile size-quota

Use **info-center security-logfile size-quota** to set the maximum size for the security log file.

Use **undo info-center security-logfile size-quota** to restore the default.

## Syntax

**info-center security-logfile size-quota** *size*

**undo info-center security-logfile size-quota**

## Default

The maximum size for the security log file is 10 MB.

## Views

System view

## Predefined user roles

network-admin

## Parameters

*size*: Sets the maximum size for the security log file, in MB. The value range is 1 to 10.

## Examples

```
# Set the maximum size to 6 MB for the security log file.  
<Sysname> system-view  
[Sysname] info-center security-logfile size-quota 6
```

## Related commands

**info-center security-logfile alarm-threshold**

# info-center source

Use **info-center source** to configure a log output rule for a module.

Use **undo info-center source** to restore the default.

## Syntax

**info-center source** { *module-name* | **default** } { **console** | **logbuffer** | **logfile** | **loghost** | **monitor** }  
{ **deny** | **level** *severity* }

**undo info-center source** { *module-name* | **default** } { **console** | **logbuffer** | **logfile** | **loghost** | **monitor** }

## Default

[Table 7](#) lists the default output rules for logs.

**Table 7 Default output rules for logs**

Destination	Log source modules	Output switch	Severity
Console	All supported modules	Enabled	Debugging

Destination	Log source modules	Output switch	Severity
Monitor terminal	All supported modules	Disabled	Debugging
Log host	All supported modules	Enabled	Informational
Log buffer	All supported modules	Enabled	Informational
Log file	All supported modules	Enabled	Informational

## Views

System view

## Predefined user roles

network-admin

## Parameters

*module-name*: Specifies a module by its name. You can use the **info-center source ?** command to view the modules supported by the device.

**default**: Specifies all supported modules.

**console**: Outputs logs to the console.

**logbuffer**: Outputs logs to the log buffer.

**logfile**: Outputs logs to the log file.

**loghost**: Outputs logs to the log host.

**monitor**: Outputs logs to the monitor terminal.

**deny**: Disables log output.

**level severity**: Specifies a severity level in the range of 0 to 7. The smaller the severity value, the higher the severity level. See [Table 2](#) for more information. Logs at the specified severity level and higher levels are allowed or denied to be output.

## Usage guidelines

If you do not set an output rule for a module, the module uses the output rule set by using the **default** keyword. If no rule is set by using the **default** keyword, the module uses the default output rule.

To modify or remove an output rule set for a module, you must use the *module-name* argument. A new output rule configured by using the **default** keyword does not take effect on the module.

If you execute this command for a module multiple times, the most recent configuration takes effect.

If you execute this command for the **default** modules multiple times, the most recent configuration takes effect.

## Examples

# Output only VLAN module's information with the emergency level to the console.

```
<Sysname> system-view
[Sysname] info-center source default console deny
[Sysname] info-center source vlan console level emergency
```

# Based on the previous configuration, disable output of VLAN module's information to the console so no system information is output to the console.

```
<Sysname> system-view
[Sysname] undo info-center source vlan console
```

# info-center synchronous

Use **info-center synchronous** to enable synchronous information output.

Use **undo info-center synchronous** to disable synchronous information output.

## Syntax

**info-center synchronous**

**undo info-center synchronous**

## Default

Synchronous information output is disabled.

## Views

System view

## Predefined user roles

network-admin

## Usage guidelines

System log output interrupts ongoing configuration operations, including obscuring previously entered commands. Synchronous information output shows the obscured commands. It also provides a command prompt in command editing mode, or a [Y/N] string in interaction mode so you can continue your operation from where you were stopped.

## Examples

# Enable synchronous information output, and then execute the **display current-configuration** command to view the current configuration of the device.

```
<Sysname> system-view
[Sysname] info-center synchronous
Info-center synchronous output is on
[Sysname] display current-
```

At this time, the system receives log information. It displays the log information first, and then displays your previous input, which is **display current-** in this example.

```
%May 21 14:33:19:425 2007 Sysname SHELL/4/LOGIN: VTY login from 192.168.1.44
[Sysname] display current-
```

Enter **configuration** to complete the **display current-configuration** command, and press the **Enter** key to execute the command.

# Enable synchronous information output, and then save the current configuration (enter interactive information).

```
<Sysname> system-view
[Sysname] info-center synchronous
Info-center synchronous output is on
[Sysname] save
```

```
The current configuration will be written to the device. Are you sure? [Y/N]:
```

At this time, the system receives the log information. It displays the log information first and then displays [Y/N].

```
%May 21 14:33:19:425 2007 Sysname SHELL/4/LOGIN: VTY login from 192.168.1.44
[Y/N]:
```

Enter **Y** or **N** to complete your input.

## info-center syslog min-age

Use **info-center syslog min-age** to set the minimum storage period for logs in the log buffer and log file.

Use **undo info-center syslog min-age** to restore the default.

### Syntax

**info-center syslog min-age** *min-age*

**undo info-center syslog min-age**

### Default

The log minimum storage period is not set.

### Views

System view

### Predefined user roles

network-admin

### Parameters

*min-age*: Sets the minimum storage period in hours. The value range is 1 to 8760.

### Examples

```
# Set the log minimum storage period to 168 hours.  
<Sysname> system-view  
[Sysname] info-center syslog min-age 168
```

## info-center syslog trap buffersize

Use **info-center syslog trap buffersize** to set the maximum number of log traps that can be stored in the log trap buffer.

Use **undo info-center syslog trap buffersize** to restore the default.

### Syntax

**info-center syslog trap buffersize** *buffersize*

**undo info-center syslog trap buffersize**

### Default

The log trap buffer can store a maximum of 1024 traps.

### Views

System view

### Predefined user roles

network-admin

### Parameters

*buffersize*: Specifies the maximum number of log traps that can be stored in the log trap buffer. The value range is 0 to 65535. Value 0 indicates that the device does not buffer log traps.

### Usage guidelines

Log traps are SNMP notifications stored in the log trap buffer. After the **snmp-agent trap enable syslog** command is configured, the device sends log messages in SNMP notifications to the log trap buffer. You can view the log traps by accessing the MIB corresponding to the trap buffer.

The default buffer size is usually used. You can adjust the buffer size according to your network condition. New traps overwrite the oldest traps when the log trap buffer is full.

## Examples

```
# Set the log trap buffer size to 2048.
<Sysname> system-view
[Sysname] info-center syslog trap buffersize 2048
```

## Related commands

**snmp-agent trap enable syslog**

# info-center timestamp

Use **info-center timestamp** to set the timestamp format for logs sent to the console, monitor terminal, log buffer, and log file.

Use **undo info-center timestamp** to restore the default.

## Syntax

```
info-center timestamp { boot | date | none }
undo info-center timestamp
```

## Default

The timestamp format for logs sent to the console, monitor terminal, log buffer, and log file is **date**.

## Views

System view

## Predefined user roles

network-admin

## Parameters

**boot**: Sets the timestamp format to xxx.yyy, where xxx is the most significant 32 bits (in milliseconds) and yyy is the least significant 32 bits. For example, 0.21990989 equals Jun 25 14:09:26:881 2007. The **boot** time shows the time since system startup.

**date**: Sets the timestamp format to MMM DD hh:mm:ss:xxx YYYY, such as Dec 8 10:12:21:708 2007. The **date** time shows the current system time.

- MMM: Abbreviations of the months in English, which could be Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, Nov, or Dec.
- DD: Date, starting with a space if it is less than 10, for example " 7".
- hh:mm:ss:xxx: Local time, with hh in the range of 00 to 23, mm and ss in the range of 00 to 59, and xxx in the range of 0 to 999.
- YYYY: Year.

**none**: Indicates no time information is provided.

## Examples

```
# Set the timestamp format to boot for logs sent to the console, monitor terminal, log buffer, and log file.
<Sysname> system-view
[Sysname] info-center timestamp boot
```

## Related commands

**info-center timestamp loghost**

# info-center timestamp loghost

Use **info-center timestamp loghost** to set the timestamp format for logs sent to log hosts.

Use **undo info-center timestamp loghost** to restore the default.

## Syntax

**info-center timestamp loghost** { **date** | **iso** [ **with-timezone** ] | **no-year-date** | **none** }

**undo info-center timestamp loghost**

## Default

The timestamp format for logs sent to log hosts is **date**.

## Views

System view

## Predefined user roles

network-admin

## Parameters

**date**: Sets the timestamp format to mmm dd hh:mm:ss yyyy, such as Dec 8 10:12:21 2007. The **date** time shows the current system time.

**iso**: Sets the ISO 8601 timestamp format, for example, 2009-09-21T15:32:55.

**with-timezone**: Includes the time zone information in the ISO format timestamp. For example, 2009-09-21T15:32:55+01:00. By default, the ISO format timestamp does not contain the time zone information.

**no-year-date**: Sets the timestamp format to the current system date and time without year.

**none**: Indicates that no timestamp information is provided.

## Examples

# Set the timestamp format to **no-year-date** for logs sent to log hosts.

```
<Sysname> system-view
```

```
[Sysname] info-center timestamp loghost no-year-date
```

## Related commands

**info-center timestamp**

# info-center trace-logfile quota

Use **info-center trace-logfile quota** to set the maximum size for the trace log file.

Use **undo info-center trace-logfile quota** to restore the default.

## Syntax

**info-center trace-logfile quota** *size*

**undo info-center trace-logfile quota**

## Default

The maximum size for the trace log file is 1 MB.

## Views

System view

## Predefined user roles

network-admin

## Parameters

*size*: Sets the maximum size for the trace log file, in MB. The value range is 1 to 10.

## Examples

```
# Set the maximum size to 6 MB for the trace log file.
<Sysname> system-view
[Sysname] info-center trace-logfile quota 6
```

# logfile save

Use **logfile save** to manually save logs in the log file buffer to the log file.

## Syntax

```
logfile save
```

## Views

Any view

## Predefined user roles

network-admin

## Usage guidelines

You can specify the directory to save the log file by using the **info-center logfile directory** command.

The system clears the log file buffer after saving the buffered logs to the log file automatically or manually.

If the log file buffer is empty, this command displays a success message event though no logs are saved to the log file.

## Examples

```
# Manually save logs from the log file buffer to a log file.
<Sysname> logfile save
The contents in the log file buffer have been saved to the file flash:/logfile/logfile.log.
```

## Related commands

```
info-center logfile enable
info-center logfile directory
```

# reset logbuffer

Use **reset logbuffer** to clear the log buffer.

## Syntax

```
reset logbuffer
```

## Views

User view

## Predefined user roles

network-admin

## Examples

```
# Clear the log buffer.  
<Sysname> reset logbuffer
```

## Related commands

**display logbuffer**

# security-logfile save

Use **security-logfile save** to manually save security logs from the security log file buffer to the security log file.

## Syntax

**security-logfile save**

## Views

Any view

## Predefined user roles

security-audit

## Usage guidelines

The system clears the security log file buffer after saving the buffered security logs to the security log file automatically or manually.

If the security log file buffer is empty, this command displays a success message event though no security logs are saved to the security log file.

To use this command, a local user must have the security-audit user role. For information about configuring the security-audit user role, see *Security Command Reference*.

## Examples

```
# Manually save the security logs in the security log file buffer to the security log file.  
<Sysname> security-logfile save  
The contents in the security log file buffer have been saved to the file  
flash:/seclog/seclog.log.
```

## Related commands

**info-center security-logfile directory**

**authorization-attribute** (*Security Command Reference*)

# snmp-agent trap enable syslog

Use **snmp-agent trap enable syslog** to enable SNMP notifications for log messages.

Use **undo snmp-agent trap enable syslog** to disable SNMP notifications for log messages.

## Syntax

**snmp-agent trap enable syslog**

**undo snmp-agent trap enable syslog**

## Default

The device does not send SNMP notifications for log messages.

## Views

System view

## Predefined user roles

network-admin

## Usage guidelines

This command enables the device to send an SNMP notification for each log message it outputs. The device encapsulates logs in SNMP notifications and then sends them to the SNMP module and the log trap buffer.

For the SNMP module to send the received SNMP notifications correctly, you must also configure SNMP on the device. For more information about SNMP configuration, see the network management and monitoring configuration guide for the device.

To view the traps in the log trap buffer, access the MIB corresponding to the log trap buffer. The log trap buffer size can be set by using the **info-center syslog trap buffersize** command.

## Examples

```
# Enable the device to send SNMP notifications for log messages.
```

```
<Sysname> system-view
```

```
[Sysname] snmp-agent trap enable syslog
```

## Related commands

**info-center syslog trap buffersize**

# terminal debugging

Use **terminal debugging** to enable display of debug information on the current terminal.

Use **undo terminal debugging** to disable display of debug information on the current terminal.

## Syntax

**terminal debugging**

**undo terminal debugging**

## Default

Display of debug information is disabled on the current terminal.

## Views

User view

## Predefined user roles

network-admin

## Usage guidelines

To enable display of debug information on the console, perform the following tasks:

1. Execute the **terminal debugging** command.
2. Enable the information center. The information center is enabled by default.
3. Use a debugging command to enable the related debugging.

To enable display of debug information on the current terminal, perform the following tasks:

4. Execute the **terminal monitor** and **terminal debugging** commands.
5. Enable the information center. The information center is enabled by default.
6. Use a debugging command to enable the related debugging.

This command takes effect only for the current connection between the terminal and the device. If a new connection is established, the default is restored.

You can also enable display of debug information on the current terminal by executing the **terminal logging level 7** command. This command has the following differences from the **terminal debugging** command:

- The **terminal logging level 7** command enables log display for all levels (levels **0** through **7**) on the current terminal.
- The **terminal debugging** command only enables display of logs with the following severity levels:
  - Debug level (level **7**).
  - Severity level higher than or equal to the level specified in the **terminal logging level** command.

## Examples

```
# Enable display of debug information on the current terminal.  
<Sysname> terminal debugging  
The current terminal is enabled to display debugging information.
```

## Related commands

**terminal logging level**  
**terminal monitor**

# terminal logging level

Use **terminal logging level** to set the lowest level of logs that can be output to the current terminal.  
Use **undo terminal logging level** to restore the default.

## Syntax

```
terminal logging level severity  
undo terminal logging level
```

## Default

The lowest level of logs that can be output to the current terminal is 6 (Informational).

## Views

User view

## Predefined user roles

network-admin

## Parameters

*severity*: Specifies a log severity level. Valid values are alert, critical, debugging, emergency, error, informational, notification, warning, and digits from 0 to 7.

## Usage guidelines

This command enables the device to output logs with a severity level higher than or equal to the specified level to the current terminal. For example, if you set the *severity* argument to 6, logs with a severity value from 0 to 6 are output to the current terminal.

This command takes effect only for the current connection between the terminal and the device. If a new connection is established, the default is restored.

## Examples

# Configure the device to output logs with the debugging level and higher levels to the current terminal.

```
<Sysname> terminal logging level 7
```

## terminal monitor

Use **terminal monitor** to enable monitoring of logs on the current terminal.

Use **undo terminal monitor** to disable monitoring of logs on the current terminal.

## Syntax

**terminal monitor**

**undo terminal monitor**

## Default

Monitoring of logs is enabled on the console and disabled on the monitor terminal.

## Views

User view

## Predefined user roles

network-admin

## Usage guidelines

This command takes effect only for the current connection between the terminal and the device. If a new connection is established, the default is restored.

## Examples

# Enable monitoring of logs on the current terminal.

```
<Sysname> terminal monitor
```

The current terminal is enabled to display logs.